



SILICONE SPRAY LUBRICANT

225601



Description

Multi-purpose lubricant. For commercial and industrial use.

Areas of use

Plastic molding: release agent for injection and compression moldings.

Packaging: prevents waxes, adhesives and plastics from sticking to heat sealer bars. Reduces clean-up time. Eliminates friction on guide rails, line conveyors, scramble tables, etc.

Convertors and printers: eliminates glue build-up on working surfaces. Reduces friction on paper cutters, knives, drills, etc.

Industrial: for industrial blenders, bins, conveyors, paper, leather, textile and paper mill dry cans, Plating screens, glass, fiber, fabric, hosiery forms, container coating for easy release of sticky contents.

Automotive: lubricates window channels, door, weather stripping, trunk seals, undercarriage, rubber mounting, emergency brakes, pedal shafts, car seats, adjustment mechanisms. Eliminates squeaks from fan belts (do not apply when running). Prevents battery terminal corrosion. Waterproofs ignition system, hinges, springs and casters.

Garment: promotes slip on sewing machine beds, cutting tables and dies. Prevents bunching of fabrics during sewing operation.

First aid

If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

If swallowed: Rinse mouth. Get medical attention if symptoms occur. If exposed or concerned: Get medical advice/attention.

Contains: (CAS No.): Trichloroethylene (79-01-6) and Carbon Dioxide (124-38-9).

To download current SDS information, please visit veritvcorp.msds.com.

Features/Benefits

Stops sticking—drawers, windows, doors, screens, zippers, and locks

Eliminates annoying squeaks in hinges, latches, springs, etc.

Retards corrosion—protects battery terminals, tools, guns, skates, aluminum windows and doors

Helps prevent grass, dirt and mud from sticking to lawn mowers—snow from sticking to snow shovels

Dries fast—leaves no greasy or oily film—not affected by water, oil or solvents

Heat stable—will not freeze or melt

Specifications

Color: Clear

Can size: 20 oz

Scent: Solvent

Net weight: 12 oz

Form: Aerosol

Shelf life: 1 year+

Regulatory

Ozone depleting compounds: None

Recyclable package: Yes

VOC compliant CARB: Yes

VOC compliant OTC: Yes

Packaging

225601: 12 cans/case