



4-WAY PENETRATING LUBRICANT

225603



Description

This heavy duty penetrant is designed to work fast. The non-conductive formula with moisture displacer, lubricates parts and never dries. Spray it on moving parts that have become stationary to loosen rust or corrosion, making it easy to separate the surfaces. Clinging foam penetrates fast to work immediately. Non-conducting up to 24,800 volts.

Areas of use

Lubricates: locks, hinges, moving parts, nuts and bolts.
Use on and in: refrigeration equipment, automobiles and workshops.

First aid

If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

If swallowed: Rinse mouth. Get medical attention if symptoms occur. If exposed or concerned: Get medical advice/attention.

Contains: (CAS No.): Trichloroethylene (79-01-6) and Carbon Dioxide (124-38-9).

To download current SDS information, please visit veritivcorp.msds.com.

Features/Benefits

- Non-conducting
- Lubricates
- Never dries
- Prevents corrosion

Specifications

- Color: Dark brown
- Can size: 20 oz
- Scent: Solvent
- Net weight: 15 oz
- Form: Aerosol
- Shelf life: 1 year+

Regulatory

- Ozone depleting compounds: None
- Recyclable package: Yes
- VOC compliant CARB: Yes
- VOC compliant OTC: Yes

Packaging

225603: 12 cans/case